

## Data Sheet

### Continuous soffit strip Ventilator

Flush solution to soffit board ventilation

#### Application

- For fitting to soffit boards to form passive air entry to roof voids
- To form clear and regulated free airspace
- To allow eaves to eaves and eaves to ridge cross flow ventilation
- To maintain 10,000mm<sup>2</sup> airflow entry

#### Product Features & Benefits

- Supplied in convenient 2.4m lengths
- Accommodates soffit board thickness 6mm – 12mm
- Integral flyscreen at 4mm
- Complies with Building Regulation Part C2
- Meets requirements of BS5250:2021 Management of moisture in building
- Lightweight and resistant to corrosion and rotting

#### Materials

- Manufactured in White recycled PVC

#### Installation Guide

- Use 10mm/10,000mm<sup>2</sup> airflow product to ventilate pitched roofs > 15 degrees when the roof void is loft space.
- Securely fix soffit strip upstand to fascia board
- Push fit pre sized soffit board into 'C' profile jaw
- Secure fix soffit board to wall in final position
- To prevent air flow blockage and/or water ponding directly above the continuous soffit ventilator, we advise to use a felt support tray to support roof membrane/felt
- The soffit ventilator should be fitted along the full length of the eaves and along both sides of the building to create required cross flow ventilation.
- For most applications consider using our 6mtr roll out rafter trays to maintain secondary airflow.

#### Product Range

Description	Ventilation	Width (vented)	Width (overall)	Length	Pack Qty
Continuous soffit strip ventilator (white)	10,000mm <sup>2</sup>	35mm	50mm	2.4m	20's
Continuous soffit strip ventilator (brown)	10,000mm <sup>2</sup>	35mm	50mm	2.4m	20's

