

Data Sheet

Heavy Green Mineral Capsheet

Description

Green Mineral is a traditional pour and roll membrane which is used as the final waterproofing layer in conjunction with an underlay membrane. It features a rag fibre base which is saturated and coated in oxidised bitumen and is finished with light sand on the lower surface and mineral granules on the upper surface.

When incorporated in a suitably designed and installed multi-layer system, maintained in accordance with BS 8217:2005 - Reinforced bitumen membranes for roofing, Green Mineral will provide reliable waterproofing performance and is suitable for use on all types of non-habitable dwellings and outbuildings.

Key features & benefits

- Cost-effective waterproofing
- Heavy grade
- Mineral finish
- UV protected

Installation

This product should be installed in accordance with manufacturer recommendations and all relevant national standards and codes of practice, including BS 8217:2005 – the code of practice for reinforced bitumen membranes for roofing.

Technical Data

Characteristic	Test Method	Result	Tolerance
Roll Length	BS EN 1848-1	10m	+/- 150mm
Roll Width	BS EN 1848-1	1m	+/- 1.5%
Roll Weight	BS EN 1849-1	32kg	+/- 5%
Straightness	BS EN 1848-1	PASS	
Visible Defect	BS EN 1850-1	PASS	
Watertightness	EN 1928:2000 Method A	PASS	