

Data Sheet

Dry Fix Hip Support Kit

Continuous support to hip tiles above dry fix vent roll with tile clips

Application

- · To form a continuous support to hip tiles up the hip of the roof
- Fitted above dry fix ridge kit vent roll
- Hip water drainage tray
- · Hip Kit to be used with additional Dry Fix ridge kit

Product Features & Benefits

- Contributes to meeting requirements of BS5534
- · Lightweight and resistant to corrosion and rotting
- Combine with vent roll from dry fix ridge vent kit

Materials

- Manufactured in Black/grey PVC
- Aluminium Clips

Installation Guide

- Build up the roof hip as normal, ensure neatly cut tiles along the hip battens are secured using long and short hip clips as required
- Once the dry fix vent roll has been installed, position the hip support trays centrally over the vent roll
- Start at the lower eaves and trim the first hip support tray to suit the overhang of the bottom course of tiles, secure in place
- Continue working up the hip with the remaining hip support trays
- Ensure a minimum 100mm overlap at each joint, ensure higher hip support trays lap over lower hip support trays
- · Continue to install hip support trays to cover full length of hip
- · Finish roof as required

Product Range

Description	Full Length	Working Length	Width	Height	Pack Qty
Dry fix Support kit contains:					
Dry fix hip support tray 1.2m	1200mm	1100mm	255mm	30mm	5
Short hip tile clips	-	-	-	-	20
Long hip tile clips	-	-	-	-	20
Short leg ratchet clips (optional use)	-	-	-	-	26

Short hip tile clips:

Used to mechanically secure the cut tiles at the intersection with adjacent tile tiles.

Long hip tile clips:

Used to mechanically hold the cut tile up from the base along the hip.



