

Data Sheet

Rhinovent Ultra



07/4456

Rhinovent Breathable Roof Tile underlays are a composite structure, manufactured by lamination of a water vapour permeable film between two layers of nonwoven spunbond polypropylene to form a flexible, vapour permeable, roof tile underlay for unsupported and fully supported specifications.

Rhinovent Breathable Roof Tile underlays are suitable for use in warm non-ventilated and cold ventilated pitched roof systems and available in two weights.

Weathertightness - As part of a complete roof, the product will resist the passage of water and wind-blown snow and dust into the interior of the building. Risk of condensation - the product can be regarded as a low water vapour resistance (Type LR) underlay and can be used as part of a non-ventilated warm and ventilated cold, roof system.

Wind loading - When installed on appropriately spaced battens the products' physical properties are deemed adequate to resist the wind loads imposed on the underlay. The product will reduce the wind uplift forces acting on the roof covering.

Strength - The product has adequate strength to resist the loads associated with the installation of the roof.

Durability - Under the normal conditions found in a roof space the product will have a service life comparable to a traditional roof tile underlay.

Stock Sizes - 1 x 50m and 1.5 x 50m

Characteristic (Units)

Thickness (mm)	0.40
Mass per unit area* (g-m ²)	112
Roll Length* (m)	50,100
Roll Width* (m)	up to 3
Colour Upper Lower	Coloured White
Tensile Strength* (N per 50mm) Longitudinal Transverse	270 155
Elongation* (%) Longitudinal Transverse	60 70
Tear Resistance* (N) Longitudinal Transverse	105 100
Resistance to penetration of air (m ² / m ² .h.50 Pa)	0.01
Watertightness * unaged aged(1)	W1 W1
Water Vapour transmission* (S)	0.029
Vapour resistance (MN.s.g ⁻¹)	0.145

